



# SHEP FARM FRESH

## VEGETABLE OIL FORM RELEASE

### DESCRIPTION

100% natural, organic chemical release agent. Ideal for sensitive environmental situations such as bridge formwork over rivers and streams or potable water reservoirs. Shep Farm Fresh provides quick, easy release and leaves an architectural bondable concrete surface.

### PRIMARY APPLICATIONS

- Chemically releases concrete from plywood, steel, aluminum, polystyrene, alkus and fiberglass forms and formliners.
- Prevents concrete build-up on all equipment.
- Cleans and reconditions forms.
- Helps eliminate build-up, bugholes, and fines.

### FEATURES & BENEFITS

- Organic
- Biodegradable
- No Petroleum
- Environmentally Friendly
- VOC Compliant
- Ready to Use
- Odorless
- Non-Staining

### DIRECTIONS FOR USE

**Application:** Stir before use. Apply in thin film for maximum protection and economy. Spread uniformly with cross spray to avoid pin holes and uncoated areas. Puddles should be wiped up with squeegee or rag prior to use of forms. Prior to coating plywood forms, apply one or two heavy brush coats to edges for waterproofing protection.

**Surface Preparation:** Forms and equipment should be free from dirt, hardened concrete and foreign matter.

**Method:** For best results, lightly fog Shep Farm Fresh using an atomizing spray tip.

**Clean-Up:** Sprayers and other application equipment can be cleaned with water.

### COMPLIANCES

- Tested and certified against NSF/ANSI 61, Section 5
- Corps of Engineers CEGS-03300, Section 10.8 Form Coating.
- Navy Dock and Piers 56359
- V.O.C. Compliant

### PACKAGING

5 gallon pails and 55 gallon drums.

### ESTIMATED COVERAGE

Steel, Aluminum, Plastic and High Density Plywood:  
1,000 -1,500 ft<sup>2</sup>/gal.

Medium Density Plywood, Paper Column Forms:  
1,000 -1,250 ft<sup>2</sup>/gal.

BB Grade Plywood: ..... 1000 ft<sup>2</sup> /gal.

Rough Sawn Lumber, Straited Plywood:

First use, 2 coats: .....500 ft<sup>2</sup>/gal./coat

Subsequent uses: ..... 1,000 ft<sup>2</sup>/gal.

### LIMITATIONS

- For subsequent coatings over concrete, follow recommended application procedures by paint and coating manufacturers.
- When any material is to be applied on top of the concrete, follow the application instructions of the manufacturer.
- Protect from freezing.

**LIMITED WARRANTY:** NOTICE - READ CAREFULLY. CONDITIONS OF SALE. Manufacturer offers this product for sale subject to, and Buyer and all users are deemed to have accepted, the following conditions of sale and limited warranty which may be varied by written agreement of a duly authorized corporate officer of Manufacturer. No other representative of or for Manufacturer is authorized to grant any warranty or to waive limitation of liability set forth below.

**Warranty Limitation:** Manufacturer warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, Manufacturer will replace the defective product with new product without charge to the purchaser. Manufacturer makes NO OTHER WARRANTY, either expressed or implied, concerning this product. There is NO WARRANTY OF MERCHANTABILITY. In no case shall Manufacturer be liable for special, indirect or consequential damages resulting from the use or handling of the product, and no claim of any kind shall be greater in amount than the purchase price of the product in respect of which damages are claimed.

**Inherent Risk:** MANUFACTURER MAKES NO WARRANTY TO THE PERFORMANCE OF THE PRODUCT AFTER IT IS APPLIED BY THE PURCHASER, AND PURCHASER ASSUMES ALL RISKS ASSOCIATED WITH THE USE OR APPLICATION OF THE PRODUCT.