



# SHEP CURE & HARD

## CONCRETE CURING COMPOUND & HARDENER

### DESCRIPTION

Shep Cure & Hard concrete curing compound was specially formulated to provide the contractor with a good, general-purpose curing compound for construction applications where economy is of prime importance. It contains no wax, resin or solvents. Shep Cure & Hard meets maximum VOC content limits of 100 g/L for Concrete Curing Compounds as required by SCAQMD Rule 1113.

### PRIMARY APPLICATIONS

Shep Cure & Hard is ideal for curing, hardening and dust-proofing exposed concrete floor slabs, sidewalks, driveways, beams, columns, etc. It can be used to provide a hard, dust-free surface on concrete floors to be painted or covered by resilient, carpeted, wood or synthetic flooring.

### FEATURES & BENEFITS

- Penetrates to cure and harden in one easy application
- Provides a low-maintenance finished surface
- Tint aids in identifying coverage
- Ideal for new or old, interior or exterior, horizontal or vertical concrete surfaces
- Dries fast and may be re-coated if desired
- Application tools may be cleaned with water
- VOC compliant -- actual VOC content is 0

### COMPLIANCES

- Meets 100g/L maximum VOC content allowed by SCAQMD Rule 1113.
- Concrete properly treated with Shep Cure & Hard is USDA accepted.

### TECHNICAL DATA

**Drying Time:** Depends on wather conditions and coverage, but will generally dry in one hour.

**Flash Point:** This product will not flash.

**Coverage:**

Broomed surface .....400 sq. ft/gal. (9.82 sq. m/L).

Troweled surface .....600 sq. ft/gal. (14.73 sq. m/L).

### DIRECTIONS FOR USE

**Preparation:** Application equipment must be clean and free of any previously used materials.

**Mixing:** For optimum performance, gentle mixing or agitation is recommended.

**CAUTION:** TO AVOID FOAMING, DO NOT MIX EXCESSIVELY.

**Application:**

**New Concrete:** Apply Shep Cure & Hard as soon as surface water has disappeared and the surface is dry to the touch or hard enough to walk on. Apply one even coat with a pressure hand sprayer or paint roller.

**Existing (Old) Concrete:** Clean surface thoroughly with a trisodium phosphate solution and rinse thoroughly. Apply Shep Cure & Hard after the surface has dried. **NOTE:** Keep heavy traffic off surface for 24 to 48 hours after applying Shep Cure & Hard.

**Cleanup:** Application equipment may be cleaned easily with soap and water while still wet.

### PACKAGING

5 gallon pails and 55 gallon drums

SHEP CURE & HARD

PRODUCT INFORMATION ■ TECHNICAL DATA SHEET

*Continued on reverse side*

## SHELF LIFE

One year in original, unopened container.

## LIMITATIONS

DO NOT DILUTE. Do not apply if the temperature of the concrete is less than 40°F (4°C). KEEP FROM FREEZING. If Shep Cure & Hard is accidentally sprayed or spilled on glass, brick, aluminum, painted surfaces, etc., flush immediately with water. Do not over-apply. DO NOT DILUTE. Do not apply if the temperature of the concrete is less than 40°F (4°C). KEEP FROM FREEZING. If Shep Cure & Hard is accidentally sprayed or spilled on glass, brick, aluminum, painted surfaces, etc., flush immediately with water. Do not over-apply.

## PRECAUTIONS

This product will not support combustion. Read and follow application information and use in accordance with the Health and Safety Information shown on the label. Refer to Material Safety Data Sheet for complete health and safety information.

**LIMITED WARRANTY: NOTICE - READ CAREFULLY. CONDITIONS OF SALE.** Manufacturer offers this product for sale subject to, and Buyer and all users are deemed to have accepted, the following conditions of sale and limited warranty which may be varied by written agreement of a duly authorized corporate officer of Manufacturer. No other representative of or for Manufacturer is authorized to grant any warranty or to waive limitation of liability set forth below.

**Warranty Limitation:** Manufacturer warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, Manufacturer will replace the defective product with new product without charge to the purchaser. Manufacturer makes NO OTHER WARRANTY, either expressed or implied, concerning this product. There is NO WARRANTY OF MERCHANTABILITY. In no case shall Manufacturer be liable for special, indirect or consequential damages resulting from the use or handling of the product, and no claim of any kind shall be greater in amount than the purchase price of the product in respect of which damages are claimed.

**Inherent Risk:** MANUFACTURER MAKES NO WARRANTY TO THE PERFORMANCE OF THE PRODUCT AFTER IT IS APPLIED BY THE PURCHASER, AND PURCHASER ASSUMES ALL RISKS ASSOCIATED WITH THE USE OR APPLICATION OF THE PRODUCT.