



1. PRODUCT AND COMPANY IDENTIFICATION

Manufacturer : W.R. Meadows, Inc.	H M I S
Address : 300 Industrial Drive	Health : 1
Hampshire, IL 60140	Flammability : 2
Telephone: (847) 683-4500	Reactivity : 0
Emergency: 1-800-424-9300 Chemtrec	Personal Protection :
Product Class : DIVISION 3; Catalog #361	
Mfg. Code I.D. : 3511000-1	
Trade Name : CS-309-25 Curing And Sealing Compound	
(Hazard Rating: 0=Least,1=Slight,2=Moderate,3=High,4=Extreme,*=Chronic)	

2. HAZARDS IDENTIFICATION

No.	Component	CAS#	% by Weight	SARA 313	VAPOR PRESSURE (mm Hg @ 20 C)	LEL (@ 25 C)
1.	Light Aromatic Naphtha	64742-95-6	50-55	NO	<10.00 @ 25 C	0.90 2.
2.	Xylene	1330-20-7	1- 5	YES	6.60	1.10
3.	1,2,4-Trimethylbenzene	95-63-6	10-15	YES	N/A	0.90 4.
4.	Ethylene Glycol Monobutyl- Ether Acetate	112-07-2	1- 5	YES	0.29	0.50@ 93C

None of the components of this product are recognized as carcinogenic. N/A: Not Applicable

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313".

3. OCCUPATIONAL EXPOSURE LIMITS

No.	PEL/TWA	OSHA		SKIN	ACGIH			SKIN
		PEL/CEILING	PEL/STEL		TLV/TWA	TLV/CEILING	TLV/STEL	
1.	N/E	N/E	N/E	N/E	N/E	N/E	N/E	NO
2.	100 ppm	N/E	N/E	N/E	100 ppm	N/E	150 ppm	NO
3.	25 ppm	N/E	N/E	N/E	25 ppm	N/E	N/E	NO
4.	N/E	N/E	N/E	N/E	N/E	N/E	N/E	YES

Skin absorption may contribute to the overall exposure to this material. Take appropriate measures to prevent skin contact.



4. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point : 322 degrees F	% Volatile by volume : N/E (Theoretical)
Evaporation Rate : < 1 (ether = 1)	% Volatile by weight : 75.00 (Theoretical)
Vapor Density : > 1 (air = 1)	Weight per gallon : 7.7 (Theoretical)
pH Level : Not Applicable	Appearance : Clear colorless liquid

5. HEALTH INFORMATION

Eye Contact: This product is presumed to be moderately irritating to the eyes. Exposure may cause corneal injury. Product vapors and/or mists may also be irritating to the eyes.

Skin Contact: Product is presumed to be moderately irritating to the skin. Prolonged contact may cause damage to the skin. Prolonged or repeated contact may result in defatting and drying of the skin which may result in dermatitis.

Inhalation: Exposure may produce irritation to the nose, throat, respiratory tract, and other mucous membranes. Exposure to excessive vapor concentrations may cause signs of transient central nervous system depression. (e.g., headache, drowsiness, loss of coordination, and fatigue). Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingestion: Product is presumed to be slightly toxic. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may result in severe lung damage. While this material has a low degree of toxicity, ingestion of excessive quantities may cause signs of central nervous system depression. (e.g., headache, drowsiness, dizziness, loss of coordination, and fatigue).

Signs and Symptoms: Symptoms of eye irritation include pain, tearing, reddening, and swelling. Symptoms of skin irritation include reddening, swelling, rash, and redness. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function. Symptoms of gastrointestinal irritation include sore throat, abdominal pain, nausea, vomiting, and diarrhea. Transient central nervous system depression may be evidenced by headache, dizziness, nausea, and symptoms of intoxication. In extreme cases unconsciousness and death may occur. Symptoms of chronic overexposure include loss of memory, loss of intellectual ability, and loss of coordination.

Aggravated Medical Conditions: Pre-existing skin, eye, and respiratory disorders may be aggravated by exposure to this product.

Other Health Effects: Based on the presence of component 4 chronic over exposure may cause damage to the red blood cells and kidneys.

6. FIRST AID MEASURES

Eye Contact: If irritation or redness develops, move victim away from exposure source and into fresh air. Flush eyes with water for fifteen (15) minutes. If symptoms persist, seek medical attention.

Skin Contact: Remove contaminated shoes and clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists seek medical attention.

Inhalation: If respiratory symptoms develop, move victim away from exposure source and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

Ingestion: Do not induce vomiting. Vomiting will cause further damage to the throat. Dilute by giving water or milk to drink if the victim is conscious. Consult a physician, hospital, or poison control center, and/or transport to an emergency facility immediately.



7. FIRE AND EXPLOSION MEASURES

Flammability Classification: NFPA: Combustible Liquid - Class II

DOT : Bulk Shipments Only: Combustible Liquid, N.O.S. (Naphtha, 1,2,4-Trimethylbenzene) NA 1993, III

Flash Point: 105 degrees F (Estimate)

Extinguishing Media: Use water fog, foam, dry chemical, or carbon dioxide.

Special fire fighting procedures and precautions: Warning. Combustible. Clear fire area of unprotected personnel. Do not enter confined fire space without helmet, face shield, bunker coat, gloves, rubber boots, and a positive pressure NIOSH approved self contained breathing apparatus.

Unusual Fire And Explosion Hazards: Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure.

8. REACTIVITY

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions And Materials To Avoid: Avoid oxidizing materials, strong acids, and strong alkalis.

Hazardous Decomposition Products: Combustion may yield Carbon Dioxide, Carbon Monoxide, and/or incomplete combustion products. Do not breathe smoke or fumes. Wear appropriate personal protective equipment.

9. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection: Use ventilation as required to control vapor concentrations - at least 10 air changes per hour are recommended for good general room ventilation. If exposure exceeds the PEL/TLV, use the appropriate NIOSH approved respirator.

Protective Clothing: Wear safety glasses, goggles, or a splash shield to prevent eye contact. Contact lenses should not be worn. Wear appropriate gloves and protective clothing to prevent contact with skin and clothing.

Additional Protective Measures: Eye wash fountains and safety showers should be available for use in an emergency.

10. ENVIRONMENTAL PROTECTION

Spill Or Leak Procedures: Large Spills: Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak only if safe to do so. Dike and contain. Remove/extinguish ignition sources. If vapor cloud forms, water fog may be used to suppress; contain run-off. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; dispose of flush solutions as above.

Small Spills: Take up with an absorbent material and place in non-leaking containers; seal tightly for proper disposal.

Waste Disposal: Observe all Federal, State and local regulations regarding proper disposal.

11. ADDITIONAL PRECAUTIONS

Keep liquid and vapor away from heat, sparks, and flame. Extinguish pilot lights, cigarettes, and turn off other possible sources of ignition prior to use and until vapors are gone. Surfaces that are sufficiently hot may ignite product in the absence of sparks or flame. Vapors may accumulate and travel to ignition sources distant from the handling site. Keep containers closed when not in use. Use



with adequate ventilation. Containers, even if empty, can contain explosive vapors. Do not cut, drill, grind or weld near containers. Containers can contain hazardous product residues even when empty. Wash with soap and water before eating, drinking, smoking or using toilet facilities.

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of the product described herein.

